

MMA ULTRA

HOBBY

1ph ~ 230V



MMA



LIFT TIG



Hot Start
Adjustable



Arc Force
Adjustable



Synergic
MMA



Anti-sticking



Voltage
Reduction
Device



Electrode
Diameter
Selection



Input
Voltage
Protection



Over-heat
Protection



Double
Fan



IGBT

Standard accessories



Electrode Holder 1.8m



Ground Clamp 1.2m



Welding Helmet



Brush

Product Parameters

Model	MMA-160 Ultra	MMA-200 Ultra
Input Voltage (V)	1~ 230	1~ 230
Frequency (Hz)	50/60	50/60
Output Current Range (A)	10-160	10-200
Absorbed Power (kVA)	7.3	9.7
Rated Input Current (A)	31.9	42.3
Effective Current (A)	17.5	23.2
No load Voltage (V)	65±5	65±5
Duty Cycle 40°C 10min	30%160A	30%200A
	60%120A	60%150A
	100%100A	100%120A
Efficiency (%)	80	80
Power factor	0.72	0.72
Insulation Class	F	F
Protection Class	IP21S	IP21S
Electrode Diameter (mm)	1.6-4.0	1.6-5.0
Gross Weight (kg)	5.2	6.4
Product Dimensions (mm)	267x108x165	322x112x178
Packaging Dimensions (mm)	307x148x255	362x152x268