

MIG 200T ULTRA

PROFI

1ph ~ 230V



**MIG
FLUX**



**MIG
CO₂ / MIX**



MMA



**TIG
LIFT**



**TIG
HF**



**Arc Force
Adjustable**



15/20KG



**Wire
1.0/1.2/1.6**



**GAS
Check**



**Wire
Check**



2T/4T



**OVER-HEAT
PROTECTION**

Product Parameters

Model	MIG-200T ULTRA		
Input Voltage (V)	1~PHASE 230		
Frequency (Hz)	50/60		
	MIG	MMA	TIG
Output Current Range (A)	20-200	10-200	10-200
Absorbed Power (kVA)	8.3	9.7	6.3
Rated Input Current (A)	36.2	42.3	27.2
Effective Current (A)	22.9	26.7	17.1
No load Voltage (V)	65±5		
	40%200A		
Duty Cycle 40°C 10min	60%160A		
	100%120A		
Efficiency (%)	80		
Power factor	0.72		
Insulation Class	F		
Protection Class	IP21S		
Electrode Diameter (mm)	0.6-1.0		
Gross Weight (kg)	14		
Product Dimensions (mm)	436x200x332		
Packaging Dimensions (mm)	475x230x420		

THREE

- MIG
- MMA
- TIG

Standard accessories



Electrode Holder And Cable



Each Clamp And Cable



MIG torch



Welding Helmet