

MIG 200T ULTRA

PROFI

1ph ~ 230V



**MIG
FLUX**



**MIG
CO₂ / MIX**



MMA



**TIG
LIFT**



**TIG
HF**



**Arc Force
Adjustable**



15/20KG



**Wire
1.0/1.2/1.6**



**GAS
Check**



**Wire
Check**



2T/4T



**OVER-HEAT
PROTECTION**

FOUR

- MIG
- MMA
- TIG
- CUT

Product Parameters

Model	MIG-200T ULTRA			
Input Voltage (V)	1~PHASE 230			
Frequency (Hz)	50/60			
	MIG	MMA	TIG	CUT
Output Current Range (A)	20-200	10-200	10-200	20-40
Absorbed Power (kVA)	8.3	9.7	6.3	5.1
Rated Input Current (A)	36.2	42.3	27.2	22.7
Effective Current (A)	22.9	26.7	17.1	14.4
No load Voltage (V)	65±5			300±20%
	40%200A			35%40A
Duty Cycle 40°C 10min	60%160A			60%35A
	100%120A			100%30A
Efficiency (%)	80			
Power factor	0.72			
Insulation Class	F			
Protection Class	IP21S			
Electrode Diameter (mm)	0.6-1.0			
Gross Weight (kg)	14			
Product Dimensions (mm)	516x200x332			
Packaging Dimensions (mm)	555x230x420			

Standard accessories



Electrode Holder And Cable



Each Clamp And Cable



MIG torch



Welding Helmet