

MIG 280 ULTRA

PROFI

3ph ~ 400V



**MIG
FLUX**



**MIG
CO₂ / MIX**



MMA



GOUGE



15/20KG



**Wire
1.0/1.2/1.6**



**GAS
Check**



**Wire
Check**



2T/4T



**Arc Force
Adjustable**

- Lightweight & Integrated:
- High Power Output
- Easy Operation
- Durable & Rugged

Product Parameters

Model	MIG-280 ULTRA		
Input Voltage (V)	3~PHASE 400		
Frequency (Hz)	50/60		
	MIG	MMA	TIG
Output Current Range (A)	30-280	10-280	10-280
Absorbed Power (kVA)	15.7	10.8	13.2
Rated Input Current (A)	22.7	15.6	19
Effective Current (A)	17.6	14.7	124.7
No load Voltage (V)	75±5		
	40%280A		
Duty Cycle 40°C 10min	60%250A		
	100%220A		
Efficiency (%)	90		
Power factor	0.72		
Insulation Class	F		
Protection Class	IP21S		
Electrode Diameter (mm)	0.6-1.2		
Gross Weight (kg)	30		
Product Dimensions (mm)	520x212x435		
Packaging Dimensions (mm)	560x250x530		

Standard accessories



Electrode Holder And Cable



Each Clamp And Cable



MIG torch



Welding Helmet